




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : A61L 9/20		A1	(11) International Publication Number: WO 97/09073
			(43) International Publication Date: 13 March 1997 (13.03.97)
(21) International Application Number: PCT/US96/14204		(81) Designated States: AL, AM, AT, AU, AZ, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).	
(22) International Filing Date: 5 September 1996 (05.09.96)			
(30) Priority Data: 08/524,284 6 September 1995 (06.09.95) US 08/647,070 9 May 1996 (09.05.96) US			
(71) Applicant: UNIVERSAL AIR TECHNOLOGY, INC. [US/US]; 28 Bowling Green Parkway, Lake Hopatcong, NJ 07849 (US).			
(72) Inventor: GOSWAMI, D., Yogi; 6025 Northwest 13th Place, Gainesville, FL 32605 (US).			
(74) Agents: BUTCH, Peter, J., III et al.; Lerner, David, Littenberg, Krumholz & Mentlik, 600 South Avenue West, Westfield, NJ 07090 (US).			
		Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>	

(54) Title: PHOTOCATALYTIC AIR DISINFECTION

(57) Abstract

A method for disinfecting an air stream containing microorganisms including the steps of providing an air stream containing microorganisms having a relative humidity greater than about 40 %; and contacting the air stream with a photocatalyst having a predetermined band gap energy coated on the upstream surface of a filter medium (28) capable of trapping bioaerosols in the presence of a source of photons (24) having a wavelength corresponding to the band gap energy of the photocatalyst, so that at least a portion of the microorganisms in the air stream are destroyed by photocatalytic oxidation. Devices embodying the method of the invention are disclosed, such as stand-alone devices (80) and devices incorporated into the HVAC systems of buildings, including the air supply registers (210). Photocatalyst-coated filter media (28) capable of trapping bioaerosols are also disclosed.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Larvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

PHOTOCATALYTIC AIR DISINFECTION

CROSS REFERENCE TO RELATED APPLICATION

This is a Continuation In Part application of U.S. Patent
5 Application Serial No. 08/524,284 by D. Yogi Goswami entitled,
"Photocatalytic System for Air Quality" received by the United States
Patent and Trademark Office on September 6, 1995, the disclosure of
which is incorporated herein by reference.

TECHNICAL FIELD

10 The present invention relates to methods for air
disinfection by photocatalytic oxidation, and, in particular, to methods
in which the air to be disinfected is provided at a relative humidity
greater than about 40%, and then contacted with a photocatalyst in the
presence of ultraviolet (UV) light so that at least a portion of any
15 microorganisms in the air are destroyed by photocatalytic oxidation.
The present invention also relates to air disinfection devices having a
photocatalyst-coated surface illuminated by a UV light source and
having means for contacting air with the photocatalyst-coated surface
and means for maintaining the relative humidity of the air above about
20 40%, so that microorganisms in the air are destroyed by photocatalytic
oxidation when the photocatalyst-coated surface is illuminated with UV
light.

Americans spend 90% of their time indoors, and while
indoors, are exposed to a variety of airborne contaminants such as
25 volatile organic compounds (VOC's), radon and biological organisms.
In a 1980 study, the Environmental Protective Agency (EPA)
concluded that indoor air pollution posed a greater health risk than
outdoor air pollution. Indoor air contamination is estimated to cause

-2-

significant increases in medical costs and a decline in work productivity.

In building circulating systems, pollutant levels from individual sources may not pose a significant risk by themselves. However, many buildings have more than one source that contributes to indoor air pollution. Illnesses resulting from such indoor pollutants are sometimes known as the "sick building syndrome." The causes of indoor air pollution are unwanted particulate matter, unwanted chemical substances and microbial contaminants. In the first two cases, conventional technology can oftentimes provide a solution by filtration and adequate ventilation. The problem of volatile organic compounds (VOCs) and microbiological contamination creates a more serious obstacle.

Because so many Americans spend a great deal of time in offices and buildings with mechanical heating, cooling, and ventilating systems, such systems pose a risk of biological contamination. In recent years, biological problems in indoor environments have received considerable attention. The Legionnaires' disease outbreak in Philadelphia in 1976 is probably the most publicized case of illness caused by indoor pollutants.

Biological contamination includes bacteria, molds, and viruses. A contaminated central air system can become a breeding ground for biological contaminants and the forced air can distribute the contaminants throughout the building.

During the past three to four decades, significant changes have occurred in the construction and operation of buildings. The building envelope has become tighter, thus less outside air is being used in heating, ventilation and air conditioning (HVAC) systems. Microbial agents are not so readily diluted by mixing with fresh air.

-3-

Energy conservation programs have resulted in buildings with moisture in the indoor environment, and that has facilitated the growth of certain types of microorganisms.

Because of neglected maintenance programs in some buildings, excessive dirt, a nutrient for microorganisms, accumulates in niches of the HVAC systems. This results in maladies referred to as building related illness, building sickness and sick building syndrome.

BACKGROUND ART

Several microbiological particle control techniques exist (including mechanical and electrostatic filters) that may be used as part of the building's forced air heating/cooling system to reduce indoor concentrations of respirable particles. Microbiological filters have been used for disinfection of air and other gases because of their low cost and ease of handling. These filters can be constructed to remove not only microorganisms but submicron particles as well. For efficient and economic operation of these filters, the aerosol content of the air to be filtered must be low. (Microorganisms, particles, or droplets of liquid dispersed in air are referred to as aerosols.) A disadvantage of such filters is that they do not permanently remove the contaminants, but just transfer them to another medium; that is, the filter. Clogging will cause high pressure drops in the duct.

One viable solution is to permanently remove the contaminant and produce nontoxic residue. UV disinfection has been widely used in the past to destroy biological contaminants and toxic chemicals.

Such UV treatment has worked well for disinfection but the indoor environment may also be contaminated with low level toxic chemicals such as formaldehyde, styrene, and toluene. Ultraviolet energy alone has proven ineffective in degrading these chemicals. For

-4-

instance, U.S. Patent 5,045,288 to Raupp and Dibble, and U.S. Patents 4,892,712; 4,966,759; and 5,032,241 to Robertson and Henderson use UV to treat fluids and gases that contain pollutants.

One alternative that has gained much attention is photocatalytic oxidation, which involves the use of a photocatalyst such as TiO_2 for the total destruction of hydrocarbons and microorganisms in water. Patel, Antibacterial Effect Of Catalyzed Radiation, Masters Thesis, University of Florida, Gainesville (1993) reports powdered TiO_2 to be capable of killing Serratia marcescens after irradiation for 60-120 minutes in water. Saito et al., J. Photochem. Photobiol. B: Biol., 14, 369-79 (1992); Matsunaga, J. Antibact. Antifungic. Agents, 13, 211-20 (1985); Nagane et al., J. Dent. Res., 68, 1696-7 (1989) and Moriaka et al., Caries. Res., 22, 230-1 (1988), report TiO_2 to be capable of killing E. coli and Lactobacillus acidophilus after aeration for 60-120 minutes in water. Wang et al., Proceedings of the First International Conference on TiO_2 Photocatalytic Purification and Treatment of Water and Air (London, Ontario, Canada, November 8-13, 1992) pp. 733-9; Wang et al., Proc. AWWA Conf. (San Antonio, TX, 1993); Savat et al., J. Catalysis, 127, 167-77 (1991) and Anderson et al., Further Catalytic Purification of Water and Air, 1, 405-20 (1993) report the gas phase detoxification of trichloroethylene (TCE) and other organic contaminants. There remains a need for a method by which microorganisms may be removed from the air.

SUMMARY OF THE INVENTION

This need is met by the present invention.

It has now been discovered that air may be disinfected of microorganisms by the photocatalytic oxidation stimulated by the action of UV light on a photocatalyst under controlled humidity conditions.

-5-

A primary objective of this invention is to provide a viable solution for indoor air purification and detoxification that can be used with new or already installed air duct systems.

Another objective of this invention is to provide a
5 relatively inexpensive detoxification reactor which can be placed within the duct system of a troubled building. The reactor units can be disposed within one or several trunk ducts of the air distribution system or a reactor can be disposed in each duct leading to a room register.

A further objective of the invention is to provide a
10 detoxification reactor unit which can be readily disposed in new circulation systems or as a modification to troubled circulation systems, or as a stand-alone air filtration unit, or as an exit ventilation system or it can be used as an exit chamber for a vacuum cleaning system.

A still further objective of the invention is to provide a
15 means by which the airflow rate through the reactor and the humidity of that airflow can be regulated so as to produce the maximum destruction efficiency of a UV light acting on a catalyst such as TiO_2 .

Another important objective of the invention is to provide a photocatalytic oxidation system that not only destroys
20 microorganisms but also decontaminates the organic chemicals, as well as odors resulting from microorganisms and volatile organic contaminants which are often times found in indoor air.

Another objective of this invention is to provide a duct coated with the catalyst that will remain free of microorganisms if a
25 light of appropriate wavelength range is incident on the catalyst coated duct surface.

A further objective of this invention is to provide stand-alone embodiments for purifying contaminated air departing from

-6-

enclosures in which certain deleterious processes take place; for example, painting enclosures.

The stand-alone embodiment, in particular, also can be utilized in hospitals, including operating room where sterility of the air is critical, doctor waiting rooms, rest rooms and in other locations where recirculation is feasible and odor-reduction and a high degree of purification are necessary to provide comfort to those using these facilities.

Therefore, in accordance with one embodiment of the present invention, a method for disinfecting an air stream containing microorganisms includes the steps of providing an air stream containing microorganisms having a relative humidity greater than about 40%; and contacting the air stream with a photocatalyst having a predetermined band gap energy in the presence of a source of photons having a wavelength corresponding to the band gap energy of the photocatalyst, so that at least a portion of the microorganisms in the air stream are destroyed by photocatalytic oxidation. Preferred methods in accordance with the present invention also control the flow rate of the air stream so that at least a portion of the microorganisms in the air stream are destroyed.

The present invention also includes devices embodying the inventive method. Thus, in accordance with another embodiment of the present invention, a device for disinfecting a quantity of air containing microorganisms is provided having a surface coated with a photocatalyst having a predetermined band gap energy; means for illuminating the photocatalyst-coated surface with a source of photons having a wavelength corresponding to the band gap energy of the photocatalyst; means for contacting the air with the photocatalyst-coated surface, and means for maintaining the relative humidity of the

-7-

air above about 40%, so that at least a portion of the microorganisms in the air are destroyed by photocatalytic oxidation upon contact with the photocatalyst when the photocatalyst-coated surface is illuminated with the UV light.

5 The methods and devices of the present invention are adapted for use within HVAC systems of buildings or as stand-alone units. Thus, according to one aspect of this embodiment of the present invention, a device is provided for disinfecting air containing microorganisms having a duct through which the air is moved; a
10 blower connected to the duct to move the air therethrough; a photocatalyst having a predetermined band gap energy disposed in the duct; a lamp disposed in sufficient proximity to the photocatalyst to illuminate the photocatalyst with a source of photons having a wavelength corresponding to the band gap energy of the photocatalyst;
15 and a humidity controller adapted to maintain the relative humidity of the air in the duct above about 40%, so that at least a portion of the microorganisms in the air are destroyed by photocatalytic oxidation upon contact with the photocatalyst when the photocatalyst is illuminated with the UV light from the lamp.

20 According to yet another aspect of this embodiment of the invention, a stand-alone device for disinfecting air containing microorganisms is provided having a chamber through which the air is moved; a blower connected to the chamber to move the air therethrough; a photocatalyst having a predetermined band gap energy
25 disposed in the chamber; a lamp positioned to illuminate the photocatalyst with a source of photons having a wavelength corresponding to the band gap energy of the photocatalyst; and a humidity controller adapted to maintain the relative humidity of the air in the chamber above about 40%, so that at least a portion of the

microorganisms in the air are destroyed by photocatalytic oxidation upon contact with the photocatalyst when the photocatalyst is illuminated with UV light.

The present invention also incorporates the discovery that
5 the useful life of filter media capable of trapping bioaerosols containing microorganisms may be extended by coating the filter media with a photocatalyst having a predetermined band gap energy. When the filter media is illuminated with a source of photons having a wavelength
10 corresponding to the band gap energy of the photocatalyst under conditions of relative humidity effective to initiate the aforementioned photocatalytic oxidation, at least a portion of the microorganisms entrapped by the filter media are destroyed, thereby purging the filter media of the entrapped bioaerosols, so that continued entrapment of
15 bioaerosols by the filter media is possible, increasing the time period between the filter changes.

According to this embodiment of the present invention, a filter medium is provided capable of trapping bioaerosols having an upstream surface to be contacted with an air stream containing microorganisms, wherein the upstream surface of the filter medium is
20 coated with a photocatalyst. Preferably, the filter medium is contained within a HEPA filter or a microporous filter.

The above and other objects, features and advantages of the present invention will become clear from the following description of the preferred embodiments considered in conjunction with the
25 accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a diagrammatic-schematic of a typical heating/cooling duct system for a building with a reactor system of this invention incorporated therein;

Figure 2 is a diagrammatic perspective view of a reactor unit for purposes of illustrating the cross-sections of other views;

Figure 3 is an exploded diagrammatic view illustrating several of principal components of the reactor unit;

5 Figures 4, 5 and 6 are longitudinal cross-sections of various embodiments of the reactor unit along the line 4-4 of Figure 2 showing the arrangement of UV lamps with respect to coated members;

Figure 7 is a longitudinal cross-sectional view of a stand-alone embodiment;

10 Figure 8 is a vertical variation of the stand-alone unit of Figure 7;

Figure 9 is a cross-section along the line 9-9 showing the UV lamps disposed about the perimeter of a duct;

15 Figure 10 is a diagrammatic perspective view illustrating the positioning of the UV lamps with respect to a catalytic insert;

Figure 11 is a longitudinal cross-sectional view of another stand-alone embodiment in accordance with the present invention;

Figure 12 is a longitudinal cross-sectional view of another stand-alone embodiment in accordance with the present invention;

20 Figure 13 is a longitudinal cross-sectional view of a catalytic insert in accordance with the present invention;

Figure 14 is diagrammatic perspective view of another embodiment of a reactor unit in accordance with the present invention;

25 Figure 15 is a diagrammatic perspective view of a catalytic insert in accordance with the present invention;

Figure 16 is a diagrammatic perspective view of a UV lamp assembly in accordance with the present invention;

Figure 17 is a diagrammatic perspective view of another embodiment of a catalytic insert in accordance with the present invention;

5 Figure 18 is a longitudinal cross-sectional view of a wall-mounted UV lamp assembly;

Figure 19 is a diagrammatic perspective view of a reactor unit employing the wall-mounted UV lamp assembly depicted in Figure 18;

10 Figures 20 and 21 are diagrammatic perspective views of alternative embodiments of reactor units in accordance with the present invention;

Figures 22 and 23 are diagrammatic perspective views of reactor embodiments of the present invention mounted in the air supply registers of HVAC systems;

15 Figure 24 depicts the destruction of Serratia marcescens by photolysis and photocatalysis at 30 % RH;

Figure 25 depicts the destruction of Serratia marcescens by photolysis and photocatalysis at 50 % RH;

20 Figure 26 depicts the destruction of Serratia marcescens by photolysis and photocatalysis at 85 % RH;

Figure 27 depicts the effect of different humidities on destruction of Serratia marcescens;

25 Figure 28 depicts the destruction of Serratia marcescens by photolysis and by photocatalysis with two different reactor configurations at 50 % RH and a UV intensity of 100 W/m²; and

Figure 29 depicts the destruction of Serratia marcescens at different UV intensities.

It should be noted that the drawings are not necessarily to scale, but that certain elements have been expanded to show more

-11-

clearly the various aspects of the present invention and their advantages.

BEST MODE OF CARRYING OUT THE INVENTION

Referring now to the drawings wherein like elements are indicated by like numerals, an apparatus in accordance with the present invention embodying the method of the present invention is shown in Figure 1 in which the numeral 10 depicts the system of this invention. In most buildings, a blower/fan causes the air from the various zones of an air conditioned space to be drawn into a duct system via inlet openings and particle/aerosol filters 12. The air then can pass over the heating coil of the furnace or the heating/cooling coil of an air conditioner/heat pump of the air conditioning unit 14. The cooling coil will act as a dehumidifier since it condenses moisture from air as it cools the air.

The fan 65 of the air handling unit 14 will force the air passing over the coils 13 and 15, into a duct system 18. In Figure 1 there is a master reactor 21 along the duct 18. In many installations this will be sufficient. However, in the embodiment of Figure 1, there is also shown a series of reactor units 22 disposed in branch lines of duct system 18.

Figure 2 diagrammatically illustrates the major components within reactor 21. These components will also be found in reactors 22. These major components are a catalyst-coated liner 29, a bank of UV lamps 24 and a catalyst-coated mesh or matrix of surfaces 28. In some instances only a coated liner or a coated mesh is used. Here both are used. For purposes of the present invention, the catalyst-coated liner and mesh are referred to collectively as catalytic inserts. The lamps preferably deliver low energy photons of the UV-A

-12-

and lower energy portion of the UV-B spectrum. A UV wavelength between about 300 and about 400 nm is preferred.

Various interiors of reactor 22 can be seen in Figures 4, 5 and 6. A bank of UV lamps 24, connected to an electrical source by way of electrical leads 25 and 26 are available to each reactor. The leads 25 and 26 are shown in Figures 5 and 6 but similar leads will be present in all embodiments. The UV rays from lamps 24, in these embodiments, strike a coated liner 29 (Figure 4) or one side of a mesh and a coated liner 29 (Figure 6) either or both of which may be coated with the photocatalyst. The UV rays may alternatively be directed to both sides of coated mesh 28 and coated liner sections 29 and 29' on each side thereof. See Figure 5.

Essentially any material capable of catalyzing photocatalytic oxidation when illuminated with a source of photons in the presence of air having a relative humidity greater than about 40% is suitable for use as a photocatalyst in the present invention. Such materials are readily identified by those of ordinary skill in the art without undue experimentation. Examples of suitable photocatalysts are semiconductor materials such as ZnO_2 , TiO_2 , and the like; however, essentially any semiconductor material or a semiconductor in combination with a noble metal or other metal such as silver may be employed. Preferably, the photocatalyst is used in combination with a source of photons including wavelengths corresponding to the band gap energy of the photocatalyst. A preferred source of photons is UV light. The preferred photocatalyst is TiO_2 , which has a band gap energy falling within the energy range of UV photons of wavelengths 300-400 nm.

The mesh 28 may be made out of any material to which a photocatalyst will adhere by conventional methods. The duct liners 29

-13-

may be made of any material that will allow the deposition and adherence of a photocatalyst on its interior surface 31 by conventional methods.

Some examples of such fibers and materials for the mesh
5 include natural fibers such as cotton and wool, man-made and synthetic
fibers such as rayon, polyester, polypropylene and Teflon, and other
materials such as flame resistant fibrous materials and carbons and all
other functional fibrous materials. The mesh 28 is constructed in a
loose woven, non-woven or knitted configuration, or a combination
10 thereof, such that it allows relative free flow of air without an
excessive pressure drop.

After passing through the reactors 22 and departing the
branch conduits 30, 32, 34 and 36, the air is directed to room registers.
Obviously, in a large building there may be several dozen conduits of
15 the 30-36 type branching from a plurality of main ducts. Each room
normally has an air return opening. The air is returned from each
room and recirculated through the system via a series of ducts depicted
by the numerals 37, 38, 39 and 40. These ducts contain the filters 12
and merge into a collector duct 42 which returns the air to the intake
20 side of the air conditioning unit 14 where it may be re-cooled or re-
heated and returned to the duct system 18.

The retention time of the circulating air in the reactor 21
over the catalyst-coated mesh 28 or the coated duct liner 29 is
important. The speed of the air within the duct system is measured by
25 way of a detector 44.

In Figure 1 a conventional flow or speed detector 44 (a
Mamac Anubar flow detector) is located in the main duct system 18.
Speed detectors are oftentimes placed within each reactor 22 and it is

that type of reactor which is described with respect to the stand-alone units described hereinafter.

The faster the air speed, the less time air will be retained over the catalytic surfaces of mesh 28 or in contact with the coated surfaces 31 of liner 29. As speed or volumetric displacement is lowered, retention time increases. As stated previously, it is usually desirable to maintain air movement throughout the building at all times. Here, air speed is adjusted for a maximum destruction of the deleterious matter by controlling the retention time over the catalytic surface.

This retention time will vary depending on the air flow rate, the size of the ducts, the area of the catalytic surface and other physical characteristics. In any event, the air speed or volume flow rate is entered into a microprocessor 62 from the detector 44. The microprocessor 62 in turn will control the speed of fan motor 64 and thus the air displacement of fan 65. The blower speed is always adjusted to provide the required residence time. For example, an air speed of approximately 70 ft/min over 2 inches thick catalytic mesh provided good disinfection and destruction rates in the experiments conducted.

Figure 14 shows a catalytic insert with a honeycomb structure having square air passages. Figure 15 shows a catalytic insert construction with circular or oval inner passages. Other geometric shapes may be substituted for the ones shown in Figures 14 and 15. The photocatalyst-coated surface area within a catalytic insert may be increased through the addition of photocatalyst-coated fins 226, as shown in Figure 17. A pleated surface may also be employed. The catalytic insert structures may be made of plastic, fiber, metal and other materials. The surface area of the mesh or the liner will depend

-15-

on the expected concentrations of the contaminants and can be determined empirically for the installation involved without undue experimentation.

The relative humidity of the circulating air is also
5 important. The relative humidity level of the air is critical for the destruction of microorganisms and must be at a level effective to enhance the destruction of at least a portion of the microorganisms by photocatalytic oxidation upon contact of the microorganisms with the photocatalyst when the photocatalyst is illuminated with UV light, that
10 is, a relative humidity greater than about 40%. A relative humidity within the range between about 40% and about 70% is preferred, with a relative humidity between about 50% and about 60% being more preferred. A relative humidity of about 50% is most preferred.

Referring to Figure 1, disposed along the length of
15 duct 18 is a humidifier/dehumidifier unit 50 (sold by Sun Chemical as Model SUN 13) controlled by a detector probe of the type sold by Mamac as Model HV-2222. If detector 52 detects that the relative humidity in the air is less than 50%, a water spray or atomizer unit 54 is caused to spray enough moisture into the air stream as a fine mist to
20 raise the relative humidity to approximately 50%. If the relative humidity is over 70%, moisture is removed by dehumidifier system here represented by cooling coil 56. Coil 56 can be a separate unit but in many instances, the coils of unit 14 can be utilized. A separate back-up coil 58 can also be provided. Dehumidification of air may be
25 achieved by condensation of water using a cooling coil as shown in Figure 1, or by other conventional techniques such as desiccant dehumidification.

The relative humidity and flow rate are preferably selected so that complete destruction of the microorganisms in the air

-16-

stream is achieved. In our experiments, a relative humidity of 50% provided complete destruction of the microorganisms present with an air speed of approximately 70 ft/min over 2 inch thick catalytic mesh in a recirculating air duct. For purposes of the present invention,
5 destroyed microorganisms are defined as microorganisms that have been completely killed, and does not include microorganisms that have been merely stunned, shocked or otherwise inactivated that are capable of being revived.

Figure 1 discloses a master reactor 21 and branch
10 reactors 22. In relatively small installations, only reactor 21 will be used. In relatively large installations only reactors 22 will be used. They are combined in Figure 1 to show that the combination can also be employed.

The reactors may be provided with their own independent
15 relative humidity and flow rate controls, so that each reactor functions as an independent photocatalytic device. Alternatively, each reactor may be adapted to the relative humidity and flow rate controls of the HVAC system in which it is installed, thereby converting the HVAC system into an apparatus in accordance with the present invention.
20 Under such circumstances, the reactor will consist essentially of a catalytic insert and a UV light source for illuminating the surface. Such devices preferably have a photocatalyst coating surface area adapted to provide sufficient contact with the circulating air at the relative humidity and air flow rate of the HVAC system to destroy at
25 least a portion of the microorganisms contained in the air.

Figures 4, 5 and 6 disclose various embodiments of lamp and catalyst location within an individual reactor 22. The UV lamps 24 are shown diagrammatically. The lamps are supported in any

conventional fashion so that UV rays are directed on their respective catalytic surfaces.

Figure 4 shows a reactor 22 in which rectangular liner catalytic insert 29 is disposed within a duct section. Its inner surface is
5 coated with TiO_2 as indicated by the numeral 31.

Figure 5 discloses a reactor 22 in which the catalytic inserts are coated liners 29 and 29', which are within the duct; and a bank or banks of UV lights 24 are disposed interiorally thereof on opposite sides of a filter/mesh 28. The UV lights 24 are shown
10 crosswise of the duct.

Where appropriate, the filter/mesh 28 of reactor 22 may be a filter medium capable of trapping bioaerosols. Such a filter medium is preferably employed in any system in which it will allow a sufficient flow of air without an excessive pressure drop. Filters
15 capable of trapping bioaerosols include HEPA filters, electrostatic filters and microporous filters. By coating the surface of the filter medium upstream of the air flow with a photocatalyst, illumination of the photocatalyst with UV light under conditions of relative humidity effective to produce photocatalytic oxidation will destroy at least a
20 portion of the microorganisms in the bioaerosols trapped in the filter. This purges the filter medium of entrapped materials, thereby extending the useful light of the filter.

Figure 6 discloses a reactor 22 in which a series of elongated UV lamps 24 are positioned crosswise of the duct and
25 adjacent to a filter medium catalytic insert 28.

Figure 9 is a reactor cross-section showing perimeter disposed UV lamps 24 within the liner 29 of the catalytic insert and adjacent to the filter 28.

-18-

The present invention also contemplates a method in which the photocatalyst-coated surface is provided in a duct section by painting the interior duct walls with the photocatalyst coating. UV lamps are then installed in the duct to illuminate the photocatalyst-coated interior duct walls.

The UV lamp assemblies for illuminating catalytic inserts may be mounted on duct walls. Figure 18 depicts a wall mounted lamp assembly 128 with aluminized reflectors 122 reflecting UV light from lamps 124. Figure 19 depicts the relationship between the wall-mounted assembly 120 and photocatalyst-coated inserts 126.

The reactors may also be installed in air supply registers of HVAC systems. Figures 22 and 23 show details of units adapted for such installation. As the air comes out of the HVAC duct, instead of going directly into the room, it is first treated by the photocatalytic disinfection method of the present invention by flowing through register 210. The unit essentially consists of a catalytic insert 212, UV light source 224 and air outlet 220. Single or multiple air outlets may be employed, depending upon the residence time required. The inside surface of the catalytic insert 212 is coated with a photocatalyst. UV lamps 224 are operated by battery or electrical power (not shown).

The UV lamps 224 and catalytic insert 212 of the register are removable. Any of the catalytic inserts depicted in the reactors of Figures 4-6 are suitable for use with the register 210.

The essentials of this invention can be utilized independently of a duct system. Such a stand-alone unit 80 is shown in Figure 7. The unit 80 includes a housing 82 having an inlet 84 and an outlet 86. Intermediate the inlet and outlet is a chamber 88 that includes a control fan 90, a humidifier 92, a dehumidifier 93, a fan motor 64 for driving fan 48, and catalytic insert 96 upon which UV

-19-

light is directed from a series of UV lamps 98. An air speed detector 99 determines the air flow displacement. A second chamber 100 is provided on the housing 82 to enclose a microprocessor 102. The electric power for the unit 80 is provided to the system through the control processor 102 via leads 104 and 106. The unit 80 may be operated without its own humidity control system if the proper humidity can be insured by an air conditioning system external to the unit 80. Alternatively, the stand-alone unit may be operated in tandem with a humidifier or dehumidifier without departing from the method or devices of the present invention. The stand-alone unit 80 may also be operated without the airspeed detector 99, if the unit 80 is designed and constructed with a constant air flow rate fan 48 matched with the cross sectional area of the housing 82 to provide the required residence time for the air flow over the catalyst.

The stand-alone unit 80 can be supported by wheels 108 so that it can be easily moved to a position within the room where it is most likely to encourage air flow circulation throughout the entire room. Also, the stand-alone unit can be utilized as an exhaust unit from a room in which undesirable fumes are present which one does not wish to exhaust into the atmosphere without treating them first. For instance, paint shops or in other industrial plants, the stand-alone unit 80 can be built into a roof or any exterior wall or it can be adapted for window support in the same fashion as a room air conditioner. In any event, contaminated air is cleansed before reaching the atmosphere.

Control and operation for the stand-alone unit is the same as that previously described. When power is supplied, the fan 48 will draw air into the inlet 84. A particulate prefilter 85 is provided to maintain the interior of the stand-alone unit free of dirt that might

-20-

damage coated mesh 96 or a coated liner if one is used in combination with a mesh. The particulate prefilter can be HEPA type, electrostatic type, or any commercially available unit. Unlike units installed in the ducts of HVAC systems, particulate prefilters may be employed with stand-alone units because in such stand-alone units the pressure drop associated with a prefilter is acceptable. In the alternative, the prefilter may be omitted if the air is reasonably free of particulates. The UV lights 98 are illuminated at the same time the fan begins to rotate.

Detector 44 will measure air speed and the information is fed to microprocessor 102. The microprocessor will then adjust the rpm of the fan to ensure the proper residence time the air is subjected to the UV light while traversing the TiO_2 -coated surfaces, whether a liner or a mesh.

While this is occurring, the humidity of the incoming air is monitored by unit 101 and that data is sent to the microprocessor. If the air has a humidity of below 40%, the wetting unit or humidifier 92 is actuated until a 50% relative humidity is obtained. If the air has a relative humidity of above 70%, the dehumidifier 93, here utilizing a heating coil 93, is actuated until the relative humidity is lowered to 50%.

Figure 8 is a vertical embodiment of a stand-alone unit. Here a particulate/aerosol filter 118 pre-screens the air. A series of UV lamps 98 are disposed opposite a catalyst-coated liner or surface 100.

Again, the fan speed is controlled by the microprocessor via motor 64 which receives the input from detector 44. Humidity is adjusted in the same manner as described in Figure 7.

As shown in Figures 11 and 12, the stand-alone units of the present invention may be adapted to receive the reactors of

Figures 4-6. The base stand-alone unit 180 of Figure 11 includes a housing 182 having an inlet 184 and outlet 186. Intermediate the inlet and outlet is a chamber 188 that includes a control fan 190 and a fan motor 164 for driving fan 148. The depicted stand-alone units are
5 operated without an air speed detector, and are instead designed and constructed with a constant air flow rate fan adapted to the cross sectional area of the stand unit housing to provide the required residence time for the air flow over the photocatalyst. Figure 12 depicts a stand-alone unit also containing a humidifier 192 and a
10 dehumidifier 194 with a flow bypass/diverter 204 controlled by microprocessor 202. The microprocessor 202 controls the flow bypass/diverter to direct the inlet air to either the humidifier, dehumidifier or directly into chamber 188, depending upon the humidity of the inlet air as measured by the microprocessor. UV lamp
15 assembly 228 illuminates catalytic insert 212 within chamber 188. Figure 6 shows the UV lamp assembly 228 of Figures 11, 12 and 14, in which a horizontal array of UV lamps 224 are arranged in frame 228 for insertion in the honeycomb structure of Figure 14.

Figure 15 depicts a catalytic insert 212 for a reactor in
20 which the insert is illuminated by UV lamp assembly located exterior to the insert. Figure 14 depicts a reactor 222 in which the UV lamp assembly 228 is located within the catalytic insert 212.

As noted above, the stand-alone units of Figures 11 and 12 are adapted to receive the reactors of Figures 4-6. Figure 13
25 depicts a reactor specially adapted for use with stand-alone units by containing a prefilter 238 that would otherwise not be suitable for use with most HVAC systems because of the pressure drop that it would produce. The reactor also includes catalytic insert 212 and a photocatalyst-coated after-filter 230. The after-filter may alternatively

be coated or impregnated with material like activated carbon or other suitable materials for absorbing VOC's, odors, and the like.

A catalytic insert 212 having a honeycomb structure with square air passages 231 and a built-in lamp assembly 228 is shown in Figure 14. Such an insert is suitable for use with the stand-alone units of Figures 11 and 12. Another suitable catalytic insert for the stand-alone unit of Figures 11 and 12 is shown in Figure 17. Catalytic insert 212 has finned wall passages 226, which serve to increase the catalytic surface area, thus increasing residence time at the same air flow rate and overall space availability. Fins 226 shown in Figure 17 are rectangular; however, they may be modified in any configuration to control the residence time per unit catalytic area.

Other catalytic inserts for the stand-alone units of Figures 11 and 12 are shown in Figures 20 and 21, which depict circular catalytic inserts 212. In Figure 20, catalytic insert 212 has a pleated surface 251 illuminated from the interior by UV lamp 224. Additional lamps may be fitted at the periphery, or other locations, if required, provided the UV light from the lamps is incident on the catalyst. Figure 21 depicts a catalytic insert 212 having a flat surface 252 of plastic strips 253 coated with catalyst 231.

Figure 15 depicts a catalytic insert 212 with a tubular construction having circular or oval air passages 232. The insert contains no UV lamps and is for use with the stand-alone unit of Figure 11 or 12 in which UV lamp assembly 228 is located in chamber 188 exterior to the photocatalyst-coated insert 212.

The following examples further illustrate the present invention, and are not to be construed as limiting the scope thereof. All parts and percentages are by weight unless expressly indicated to be otherwise, and all temperatures are in degrees Celsius.

-23-

EXAMPLESMATERIALS AND METHODS

Photolytic and photocatalytic experiments were conducted to determine the effect of catalyzed UV radiation on airborne microorganisms. By trial and error, a correct dilution of Serratia marcescens was found which gave appropriate counts on agar plates. 20 milliliters of the diluted Serratia culture was transferred into a nebulizer which was operated by 99.999% pure compressed nitrogen at 30 to 40 psi.

10 The experimental apparatus consisted of a reactor test section, recirculation duct and a blower. The first four feet of the duct was rectangular in cross-section. This section was attached to nebulizers, one of which contained the diluted Serratia culture, and the other, pure deionized water.

15 Appropriate air flow through the nebulizer was determined, so that aerosols did not fall to the surface of the duct. Thermocouples and pressure taps were attached to this section to measure the temperature of the air stream before the reactor and the pressure drop across the reactor, respectively.

20 The second section of the apparatus consisted of the reactor area which housed 24 UV lamps and a Fiberglass filter coated with titanium dioxide and arranged perpendicular to the air flow. This section was 32 inches long, with a cross-sectional area of 400 in².

The UV lamps used were low pressure mercury lamps
25 (Southern New England RPR-3500A) with an input energy of 14 W. Each lamp emitted approximately 1.5 W of UV-radiation, predominately at 350 nm. The UV light was measured by placing an Eppley radiometer (Model TUVR) perpendicular to the UV lamp at different distances.

Air sampling was conducted at a distance of one foot from the reactor. Four culture plates securely placed on a rack were used to capture viable organisms over a 30 second interval. Thermocouples were attached to this section to measure the temperature.

5 The recirculating section of the duct consisted of a circular duct with a diameter of one foot. A humidity probe was attached to this section to measure the relative humidity of the air stream. The final part of the apparatus was a blower which was connected to both the circular cross-section duct and the rectangular
10 cross-section duct. The total length of the recirculating test apparatus was 29.5 feet.

The culture plates were prepared using plate count agar, which was selected because it contained seaweed extract with the addition of some nutrients that fulfilled the nutritional requirements for
15 the growth of Serratia bacteria.

Culture plates were prepared by weighing sufficient agar powder on an electronic scale to make a half-liter solution. Agar powder (11.75 grams) was poured into a 500 mL flask of deionized water. The solution was mixed and heated for 10 to 15 minutes with a
20 magnetic stirrer and heater. After the agar powder had completely dissolved, the flask was covered with aluminum foil to prevent airborne contamination, and put into an Autoclave steam sterilizer for 30 minutes for sterilization.

After sterilization, the agar was allowed to cool for ten
25 minutes in a water bath at a temperature of 50°C. The agar was poured into petri dishes using an aseptic technique in a laminar flow hood which was cleaned with isopropyl alcohol prior to use. 500 mL of agar was poured into the petri dishes, completely covering the bottom of the dish. The dishes were set to gel on the aseptic hood for

-25-

24 hours, and then stored upside-down in the refrigerator to prevent the condensate from contacting the agar. The agar plates were used within 48 hours to prevent low level contamination.

The titanium dioxide-coated Fiberglass filter was prepared by coating the TiO_2 on a standard 16 x 25 x 2 inch Fiberglass air conditioning filter. The TiO_2 (Degussa P 25) was primarily anatase, with a BET surface area of $50 \text{ m}^2/\text{g}$ and an average particle size of 21 nm.

A thick slurry of TiO_2 was made by mixing 50 grams of TiO_2 powder and deionized water. The TiO_2 solution was mixed well by placing the flask with the thick TiO_2 slurry on a magnetic stirrer. Using a foam brush, TiO_2 was coated on both sides of the filter. The filter was allowed to dry for six hours, then another coat of TiO_2 was applied on the filter. After the filter was completely dry and the TiO_2 was sufficiently affixed, it was placed in the recirculating duct. Operation of the reactor with the TiO_2 -coated filter in place is denoted as Configuration A.

Several experiments were performed utilizing a coated surface reactor configuration (Configuration B) instead of the Fiberglass filter configuration (Configuration A). The coated surface reactor was used to increase the area for the reaction. The area which was coated with TiO_2 was approximately 720 in^2 . The duct was coated by preparing the TiO_2 slurry described above and using a foam brush to coat the surface of the duct with the TiO_2 slurry. A heat gun was used to dry the surface. After 8 hours, the surface was coated again, and dried with a heat gun.

Relative humidity and UV intensity parameters were investigated to determine the optimum conditions for the destruction of

-26-

bacteria. The humidity was varied from 30% RH to 85% RH, and the UV intensity was varied from 20 W/m² to 100 W/m².

In the humidity experiments, the air was humidified by atomizing deionized water into the duct. The air flow inside the duct was kept constant at 74 ft/min, and the UV was kept constant at 100 W/m². A humidity probe (Mamac Humidity Sensor) was attached to the duct to monitor the relative humidity (RH) of the air stream inside the duct. A silica based desiccant material was placed inside the duct to lower the humidity when needed.

The blower was turned on and allowed to stabilize for 10 to 20 minutes before the culture was atomized. All of the liquid bacterial culture in the nebulizer was allowed to completely atomize and stabilize before the initial sample was taken. After the initial sample was taken, the UV lamps were turned on and initial temperature and humidity data were recorded. Four samples were collected on agar plates at predetermined time intervals. The agar plates were exposed to the contaminated air stream for 30 seconds for collection of bacteria. Samples collected during the time intervals were kept in a relatively sterile environment to avoid contamination for the duration of the experiment. After the completion of the experiments, samples were placed upside-down in an incubator at a temperature of 30°C for 24 hours of incubation. After 24 hours of incubation, the bacterial colonies were quantified on a colony counter having a magnified lens and grid lines which facilitated an accurate count of bacterial colonies.

After the experiment was completed, the duct was cleaned to avoid contamination. Formaldehyde solution was atomized by the nebulizer into the system to decontaminate the duct. The blower was allowed to run in an air-tight duct for two hours. After this process,

-27-

the top of the duct was left open to outside air for 12 hours before starting the next set of experiments.

EXAMPLE 1

EFFECT OF RELATIVE HUMIDITY

5 Both photolysis (UV only, no TiO_2) and photocatalysis experiments were performed at relative humidities of 30%, 50% and 85%. Figures 24-26 depict the destruction of Serratia by photolysis and photocatalysis at 30% RH, 50% RH and 85% RH, respectively. At 30% RH, no significant difference was observed between photolysis
10 and photocatalysis and complete destruction of the microorganisms was not achieved. This may be attributable to insufficient H_2O to transfer the necessary hydroxyl radicals or superoxides to the bacterium. At 30% RH, it can be inferred that most of the bacterial destruction was attributable to the UV photons attacking the bacteria (photolysis). At
15 50% RH, the destruction rate for the first three hours was the same for both photolysis and photocatalysis; but after three hours, the destruction rate for photocatalysis was much greater as a result of which 100% inactivation of bacteria was achieved in about 13 hours.

RH was further increased to 85% to determine if a further
20 increase in water vapor would increase the destruction rate. However, higher RH did not increase the destruction of the bacteria. One possible explanation is that the high humidity may induce reactivation of organisms. A comparison of photocatalysis effectiveness for 30%, 50% and 85% RH is shown in Figure 27. The numerical values for
25 bacteria destruction are set forth in the Table below:

Estimated Lethal Doses At Various Humidities

PHOTOLYSIS EXPERIMENTS

5	RH	LD₅₀ W•min/m²	LD₇₅ W•min/m²	LD₁₀₀ W•min/m²
	30%	1660	3320	-----
	50%	1470	3870	-----
	85%	1900	5010	-----

10

PHOTOCATALYSIS EXPERIMENTS

WITH CONFIGURATION A

15	RH	LD₅₀ W•min/m²	LD₇₅ W•min/m²	LD₁₀₀ W•min/m²
	30%	1643	3310	-----
	50%	1210	2178	6092
	85%	1107	1660	-----

PHOTOCATALYSIS EXPERIMENTS

WITH CONFIGURATION B

20	RH	LD₅₀ W•min/m²	LD₇₅ W•min/m²	LD₁₀₀ W•min/m²
	30%	2215	5530	-----
	50%	870	1190	876

25 Notes:

1. Dose = UV Intensity • Time
2. Dashed line signifies that destruction did not occur.

-29-

As reflected in the above table, the humidity experiments were repeated with Configuration B. Because a greater photocatalysis surface area was present in this configuration, lower dosages of UV energy were needed to attain the indicated levels of destruction.

5 100% bacteria destruction was not obtained using photolysis alone, regardless of the RH level. In both Configuration A and Configuration B, 100% bacteria destruction was only obtained at an RH level of 50%. 100% destruction was not obtained at 30% or 85% RH for Configuration A or for 30% RH for Configuration B. A
10 comparison of Configuration A to Configuration B and photolysis (UV only) at 50% RH is shown in Figure 28.

EXAMPLE 2

EFFECT OF UV INTENSITY

Photocatalysis experiments were performed at the
15 aforementioned intensity levels. The RH was kept at 50% and air flow rate at 74 ft/min. The results are depicted in Figure 29.

It is evident from these results that higher UV intensity results in higher destruction rates. After 8 hours of radiation, the photocatalytic destruction rates for 100 W/m² started to level off. For
20 lower intensities, the destruction was actually increasing after 6 hours of exposure. This probably indicated that the bacteria weakened after irradiation and became vulnerable to photons and hydroxyl radical attack after 6 hours even at lower radiation levels.

Titanium dioxide in the presence of UV radiation thus
25 enhances the destruction rate of microorganisms, with complete destruction occurring at 50% RH. At low RH (30%), titanium dioxide did not accelerate the bacterial destruction. At higher RH (85%), 10% of the organisms were still viable.

-30-

The foregoing examples and description of the preferred embodiment should be taken as illustrating, rather than as limiting, the present invention as defined by the claims. As will be readily appreciated, numerous variations and combinations of the features set forth above can be utilized without departing from the present invention as set forth in the claims. All such modifications are intended to be included within the scope of the following claims.

INDUSTRIAL APPLICABILITY

Devices in accordance with the present invention are useful for the detoxification of microorganism contaminated buildings and building ventilation systems.

-31-

WHAT IS CLAIMED IS:

1. A method for disinfecting an air stream containing microorganisms, characterized by:
providing an air stream containing microorganisms
5 having a relative humidity greater than about 40%; and
contacting said air stream with a photocatalyst having a predetermined band gap energy coated on the upstream surface of a filter medium (28) capable of trapping bioaerosols, in the presence of a source of photons (24) having a wavelength
10 corresponding to said band gap energy of said photocatalyst, characterized in that at least a portion of said microorganisms in said air stream are destroyed by photocatalytic oxidation.
2. The method of claim 1, further characterized by the step of controlling the flow rate of said air stream so that said
15 microorganisms are completely destroyed.
3. The method of claim 1, characterized in that said relative humidity is between about 40 and about 70%.
4. The method of claim 3, characterized in that said relative humidity is about 50%.
- 20 5. The method of claim 1, characterized in that said photocatalyst is a semiconductor.
6. The method of claim 5, characterized in that said semiconductor is TiO_2 .
7. The method of claim 1, characterized in that said
25 source of photons (24) comprises UV light having a wavelength between about 300 and about 400 nm.
8. The method of claim 1, characterized in that said filter medium (28) is disposed transverse to the flow of said air stream.

-32-

9. A device for disinfecting a quantity of air containing microorganisms, characterized by:

a photocatalyst having a predetermined band gap energy coated on the upstream surface of a filter medium (28) capable
5 of trapping bioaerosols positioned to be in contact with said air;

means for illuminating said photocatalyst-coated filter medium with a source of photons (24) having a wavelength corresponding to said band gap energy of said photocatalyst;

means (65) for contacting said air with said
10 photocatalyst-coated filter medium; and

means (50) for maintaining the relative humidity of said air above about 40%, characterized in that at least a portion of said microorganisms in said air are destroyed by photocatalytic oxidation upon contact with said photocatalyst when said photocatalyst-coated
15 filter medium (28) is illuminated with said source of photons (24).

10. The device of claim 9, further characterized by means for controlling the flow rate of said air (62), so that the residence time of said air with said photocatalyst is effective for complete destruction of said microorganisms in said air.

20 11. The device of claim 9, characterized in that said photocatalyst is a semiconductor.

12. The device of claim 11, characterized in that said semiconductor is TiO_2 .

25 13. The device of claim 9, characterized by a HEPA filter containing said photocatalyst-coated filter medium (28).

14. The device of claim 9, characterized by a microporous filter containing said filter medium (28).

-33-

15. The device of claim 9, characterized in that said source of photons (24) comprises UV light having a wavelength between about 300 and about 400 nm.

16. A device for disinfecting air containing
5 microorganisms characterized by:

a duct (18) through which said air is moved;

a blower (65) connected to said duct to move said
air therethrough;

a photocatalyst having a predetermined band gap
10 energy disposed in said duct (18) on the upstream surface of a filter medium (28) capable of trapping bioaerosols positioned to be in contact with said air;

a lamp (24) disposed in sufficient proximity to said photocatalyst to illuminate said photocatalyst with a source of photons
15 having a wavelength corresponding to said band gap energy of said photocatalyst; and

a humidity controller (50) adapted to regulate the relative humidity of said air in said duct (18) above about 40%, characterized in that at least a portion of said microorganisms in said
20 air are destroyed by photocatalytic oxidation upon contact with said photocatalyst when said photocatalyst is illuminated with said source of photons from said lamp (24).

17. The device of claim 16, characterized in that said humidity controller (50) is adapted to regulate the relative humidity of
25 said air in said duct (18) within a range effective to completely destroy said microorganisms.

-34-

18. The device of claim 16, characterized in that said humidity controller (50) is adapted to maintain the relative humidity of said air in said duct between about 40% and about 70%.

19. The device of claim 16, characterized in that said
5 photocatalyst is a semiconductor.

20. The device of claim 19, characterized in that said semiconductor is TiO_2 .

21. The device of claim 16, characterized by a HEPA filter containing said photocatalyst-coated filter medium (28).

10 22. The device of claim 16, characterized by a microporous filter containing said photocatalyst-coated filter medium (28).

23. The device of claim 16, characterized in that said photocatalyst is additionally coated on at least one interior wall of said
15 duct (18).

24. The device of claim 16, characterized in that said photocatalyst is additionally coated on at least one interior wall (31) of a liner (29) inserted in said duct (18).

25. The device of claim 24, characterized in that at
20 least one inside wall (31) of said duct liner (18) has fins (226) affixed to the surface thereof coated with said photocatalyst, thereby increasing the photocatalyst-coated surface area of said duct liner (29).

26. The device of claim 16, characterized in that said source of photons (24) comprises UV light having a wavelength
25 between about 300 and about 400 nm.

27. The device of claim 16, further characterized by a humidity detector (52) disposed in said duct (18).

-35-

28. The device of claim 27, further characterized by a microprocessor (62) adapted to control said humidity controller (50) based on information received from said humidity detector (52).

29. The device of claim 28, further characterized by an
5 air speed detector (44) disposed in said duct (18), wherein said microprocessor (62) is further adapted to control the speed of said blower (65) based on information received from said air speed detector (44).

30. The device of claim 16, further characterized by an
10 air speed detector (44) disposed in said duct (18).

31. The device of claim 30, further characterized by a microprocessor (62) adapted to control the speed of said blower (65) based on information received from said air speed detector (44).

32. The device of claim 31, further characterized by a
15 humidity probe (52) disposed in said duct (18), wherein said microprocessor (62) is further adapted to control said humidity controller (50) based on information received from said humidity probe (52).

33. The device of claim 16, further characterized by a
20 microprocessor (62) adapted to control said humidity controller (50).

34. The device of claim 16, further characterized by a microprocessor (62) adapted to control the speed of said blower (65).

35. The device of claim 16, characterized in that said duct (18) is part of a heating, ventilation and air conditioning system.

25 36. The device of claim 35, characterized in that said blower (65) is part of a heating, ventilation and air conditioning system.

-36-

37. The device of claim 35, characterized in that said humidity controller (50) is part of a heating, ventilating and air conditioning system.

38. The device of claim 16, further characterized by a
5 filter medium downstream of said photocatalyst (230) in contact with said air moving through said duct (18) and capable of absorbing a material selected from the group consisting of volatile organic contaminants and odors.

39. A device for disinfecting air containing
10 microorganisms characterized by:

a photocatalyst having a predetermined band gap energy coated on the upstream surface of a filter medium (28) capable of trapping bioaerosols and disposed in the air supply register (210) of a heating, ventilating and air conditioning system to be contacted with
15 air moving therethrough; and

a lamp (24) positioned in sufficient proximity to said photocatalyst to illuminate said photocatalyst with a source of photons having a wavelength corresponding to said band gap energy of said photocatalyst;

20 characterized in that said heating, ventilating and air conditioning system has a blower (65) to move air through said air supply register (210) and a humidity controller (50) adapted to maintain the relative humidity of said air in said heating, ventilating and air conditioning system above about 40%, so that at least a portion of said
25 microorganisms in said air are destroyed by photocatalytic oxidation upon contact with said photocatalyst when said photocatalyst is illuminated with said source of photons (24).

40. The device of claim 39, characterized in that said humidity controller (50) is adapted to maintain the relative humidity of

-37-

said air in said heating, ventilating and air conditioning system between about 40% and about 70%.

41. The device of claim 39, characterized in that said photocatalyst is a semiconductor.

5 42. The device of claim 41, characterized in that said semiconductor is TiO_2 .

43. The device of claim 39, characterized by a HEPA filter containing said filter medium (28).

10 44. The device of claim 39, characterized by a microporous filter containing said filter medium (28).

45. The device of claim 39, characterized in that said photocatalyst is additionally coated on at least one interior surface (31) of a liner (29) inserted in said register (210).

15 46. The device of claim 45, characterized in that said at least one inside surface (31) of said liner (29) has fins (226) affixed to the surface thereof coated with said photocatalyst, thereby increasing the photocatalyst-coated surface area of said liner (29).

20 47. The device of claim 39, characterized in that said source of photons (24) comprises UV light having a wavelength between about 300 and about 400 nm.

48. The device of claim 39, further characterized by a filter medium downstream of said photocatalyst (230) in contact with said air moving through said duct (18) and capable of absorbing a material selected from the group consisting of volatile organic
25 contaminants and odors.

49. A filter medium (28) capable of trapping bioaerosols characterized by an upstream surface to be contacted with an air stream containing microorganisms, wherein said upstream surface of said filter medium (28) is coated with a photocatalyst.

-38-

50. The filter medium (28) of claim 49, characterized in that said photocatalyst is a semiconductor.

51. The filter medium (28) of claim 50, characterized in that said semiconductor is TiO_2 .

5 52. A HEPA filter characterized by said filter medium (28) of claim 49.

53. A microporous filter characterized by said filter medium (28) of claim 49.

10 54. A stand-alone device (80) for disinfecting air containing microorganisms characterized by:

a chamber (88) through which said air is moved;

a blower (90) connected to said chamber (88) to move said air therethrough;

15 a photocatalyst having a predetermined band gap energy coated on the upstream surface of a filter medium (28) capable of trapping bioaerosols and disposed in said chamber (88) to be contacted with said air moving therethrough;

a lamp (24) positioned to illuminate said photocatalyst with a source of photons having a wavelength
20 corresponding to said band gap energy of said photocatalyst; and

a humidity controller (92) adapted to maintain the relative humidity of said air in said chamber (88) above about 40%, characterized in that at least a portion of said microorganisms in said air are destroyed by photocatalytic oxidation upon contact with said
25 photocatalyst when said photocatalyst is illuminated with said source of photons (24).

-39-

55. The device (80) of claim 54, characterized in that said humidity controller (92) is adapted to maintain the relative humidity of said air in said chamber (88) above about 40%.

56. The device (80) of claim 54, characterized in that
5 said photocatalyst is a semiconductor.

57. The device (80) of claim 56, characterized in that said semiconductor is TiO_2 .

58. The device (80) of claim 54, characterized by a HEPA filter containing said filter medium (28).

10 59. The device (80) of claim 54, characterized by a microporous filter containing said filter medium (28).

60. The device (80) of claim 54, characterized in that said photocatalyst is additionally coated on at least one interior surface of said chamber (88).

15 61. The device (80) of claim 54, characterized in that said photocatalyst is additionally coated on at least one interior surface of a liner (212) inserted in said chamber (88).

62. The device (80) of claim 61, characterized in that said at least one inside surface of said liner (212) has fins (226) affixed
20 to the surface thereof coated with said photocatalyst, thereby increasing the photocatalyst-coated surface area of said liner (212).

63. The device (80) of claim 54, characterized in that said source of photons (24) comprises UV light having a wavelength between about 300 and about 400 nm.

25 64. The device (80) of claim 54, further characterized by an air speed detector (99) disposed in said chamber (88).

65. The device (80) of claim 54, further characterized by a microprocessor (102) adapted to control the speed of said

-40-

blower (90) based on information received from said air speed detector (99).

66. The device (80) of claim 65, further characterized by a humidity probe (101) disposed in said chamber (88), characterized
5 in that said microprocessor (102) is further adapted to control said humidity controller (92) based on information received from said humidity probe (101).

67. The device of claim 54, further characterized by a humidity probe (101) disposed in said chamber (88).

10 68. The device of claim 67, further characterized by a microprocessor (102) adapted to control said humidity controller (92) based on information received from said humidity probe (101).

69. The device of claim 54, further characterized by a microprocessor (102) adapted to control said humidity controller (92).

15 70. The device of claim 54, further characterized by a microprocessor (102) adapted to control the speed of said blower (90).

71. The device of claim 54, further characterized by a filter medium downstream of said photocatalyst (230) in contact with said air moving through said chamber (88) and capable of absorbing a
20 material selected from the group consisting of volatile organic contaminants and odors.

1/15

FIG. 1





FIG. 3

FIG. 2






FIG. 4




FIG. 5




FIG. 6






FIG. 8

FIG. 10



4/15

FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16





FIG. 17



7/15

FIG. 18





FIG. 19



8/15

FIG.20





FIG.21



9/15

FIG. 22






FIG. 23




10/15

FIG.24




11/15

FIG.25




12/15

FIG.26




13/15

FIG.27




14/15

FIG. 28



15/15

FIG.29



INTERNATIONAL SEARCH REPORT

International application No.
PCT/US96/14204**A. CLASSIFICATION OF SUBJECT MATTER**

IPC(6) :A61L 9/20

US CL :422/22, 24, 121, 122

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 422/22, 24, 121, 122, 186.03

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US, 5,397,552 A (WEIGOLD ET AL.) 14 MARCH 1995, see entire document.	1-71
Y	US 5,151,252 A (MASS) 29 SEPTEMBER 1992, see entire document.	1-71

☐ Further documents are listed in the continuation of Box C. ☐ See patent family annex.

* Special categories of cited documents:	*T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
*A document defining the general state of the art which is not considered to be of particular relevance	*X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
*E earlier document published on or after the international filing date	*Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
*L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	*G document member of the same patent family
*O document referring to an oral disclosure, use, exhibition or other means	
*P document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search

04 DECEMBER 1996

Date of mailing of the international search report

06 JAN 1997

Name and mailing address of the ISA/US
Commissioner of Patents and Trademarks
Box PCT
Washington, D.C. 20231

Facsimile No. (703) 305-3230

Authorized officer

TIMOTHY M. MCMAHON

Telephone No. (703) 308-0651

Form PCT/ISA/210 (second sheet)(July 1992)*